



## STANDARD SPECIFICATIONS: ALUMATECH FRAMELESS END DUMP

CUBIC YARD CAPACITY	39'	38'	37'	36'	35'	34'	32'	30'	28'	26'	24'
57" Side Height	41.4	40.3	39.2	38.0	36.9	35.8	33.5	31.2	29.0	26.7	24.4
60" Side Height	44.1	42.9	41.7	40.5	39.2	38.0	35.6	33.2	30.8	28.4	26.0
63" Side Height	46.7	45.4	44.2	42.9	41.6	40.3	37.7	35.2	32.6	30.0	27.5

### BODY

- Lengths** 24' - 39'
- Side Heights** 57" Std (60", 63" Optional)
- Sheet** 5454 H34 Aluminum Alloy  
 3/16", (.190) Side Thickness, Polished Finish  
 1/4", (.250) Floor Thickness  
 1/4", (.250) Nose (5454 H32)
- Extrusions** All 6061 T6 Aluminum Alloy  
 Top Rail: 10" x 6" Shedding  
 Quarter Rail: 8" Triangular Interlocking Sheet  
 HD Tailgate Frame-braces 5" Wide x 4" Deep Tube

### TAILGATE

- Locking Over-Center Latches
- 12 Degree Slope, Overslung Hinges
- Replaceable Rubber Seal
- 3/16", (.190) Aluminum Sheet
- Air Operated, Switch at front of Subframe

### OTHER

- LED Lights, 3 per Side
- Side Turn Signal, LED
- Stop Turn Tail 2 per Side, LED
- Sealed Wire Harness
- Ladder at Rear, Road Side

### CHASSIS / UNDERBODY

- INTRAAX Air Ride Tandem suspension, 50,000 Lb. capacity
- All Aluminum Subframe
- 102" Axle Width (77 1/2" Track) large spindles
- 10-hole, Hub-piloted Duralite Hubs
- Outboard X30 Lightweight Drums
- WABCO 4S/2M ABS
- 16.5" x 7" Brakes, Premium Lining, automatic slack adjusters
- 14 Ply Radial Tires, trailer tread, choice of size
- Aluminum Wheels, (8), 4 Polish / 4 Mill Finished
- Kingpin Setting At 10" ahead of Floor Sheet
- T-1 Steel Coupler Plate, with 5" Wide Saddles
- Aluminum Apron, 16" over Set-back Suspension
- Aluminum Draft Arms With nonload-Bearing Drop Legs
- Single Acting 5-stage Telescopic hydraulic cylinder (mounted outside)
- Rear Aluminum Fenders with short tandem fenders & flaps

CALL US FOR A DEALER NEAR YOUR AREA

EFFECTIVE 12/01/2011

WWW.TRAVISTRAILERS.COM

IN A WORLD OF TRAILERS,  
 TRAVIS LEADS.

INFO@TRAVISTRAILERS.COM

CORPORATE & SOUTHWEST  
 (800) 535-4372

SOUTHEAST & CENTRAL  
 (800) 622-3867

WEST & MOUNTAIN WEST  
 (800) 298-2178